LEDVANCEUS.COM







The LEDVANCE Value Class Dual Selectable T-FIT[™] are an innovative solution for illuminating offices, conference rooms, restaurants and retail areas. This innovative product designs responds to many logistical and aesthetic concerns with traditional panels. Easy to assemble and easy to install, this product fits in the existing T-grid ceiling. Offered in 120-347V and with lumen and CCT selectability, this product drastically reduces shipping and handling expenses as well as recycling costs.



VALUE CLASS

For more information, visit www.ledvanceUS.com/luminaires

LEDVANCEUS.COM



LEDVANCE LLC

181 Ballardvale Street, Suite 203 Wilmington, MA 01887 USA Phone 1-800-LIGHTBULB (1-800-544-4828)



ORDERING GUIDE

PANELBAR	1A	S/XX	UNH	D	8	SC7	xx	wн
Product Name PANELBAR = LED Panel Bars	Generation 1A = Generation 1A	Wattage S35 = 25, 30, or 35W S45 = 35, 40, or 45W	Voltage UNH = 120-347V	$\begin{array}{l} \text{Dimming} \\ \text{D} = 0\text{-}10\text{V} \end{array}$	CRI 8 = >80	Color Temperature SC7 = 3500K, 4000K, and 5000K	Dimensions $14 = 1 \times 4$ $22 = 2 \times 2$ $24 = 2 \times 4$	$\begin{array}{l} \text{Color/Finish} \\ \text{WH} = \text{White} \end{array}$

CONTRACTOR BENEFITS

- Optimized packaging drastically reduces shipping, handling, and recycling costs
- Decorative replacement tiles are available for applications in which scrapping the existing ceiling tile is desired
- EMBB compatible with optional field installable accessories

ACCESSORIES

Emergency Battery Back-Up Unit Mounted



Replacement Tiles



BENEFITS AND FEATURES

- Innovative, modern and sustainable design that delivers the same specifications of a regular flat panel
- Dual selectability enabled via the switches located on the driver increases the variety of applications and allows for on-site lighting adjustments
- 3500K, 4000K, and 5000K selectable color temperatures
- Offered in three selectable sizes
 - 1x4 and 2x2 models: 25, 30, or 35W
 - 2x4 model: 35, 40, or 45W
 - Three lumen outputs in one product
- Simple and easy to install, the four bars connect with a click and fits into existing T-grid ceilings
- Up to 113 LPW
- CRI >80
- Energy savings up to 60%

Scan the QR tag to view or download additional product information

